

Exhaust Arm

- » Flexible operation
- » Up to 4 m reach



Benefits

- » Fast operation due to particularly flexible adjustment
- » 40% less adjustment of the exhaust arm needed due to exhaust hood design
- » User-friendly due to particularly smooth movement of the hood with one hand
- » Arm keeps position due to self-supporting design
- » Due to its easy movement, the exhaust arm can be brought into any permanent position with one hand
- » Various options to connect the exhaust arms to fans, stationary devices or via duct work to central extraction and filtration systems

Applications

- » For connection to fans or central extraction systems
- » High levels of smoke and dust
- » Non-stop operation
- » Welding fumes, gases, vapours, light dusts, car exhaust fumes

Properties

- » 360 degrees rotating exhaust hood with damper
- » Self-supported by internal springs
- » Exhaust arms up to 4 m
- » Rotating exhaust hood

Scope of supply

- » Exhaust arm with hood
- » Wall bracket

Technical Data

Additional information	
Diameter extraction arm	150 mm
Joints	1

Order Data

Art. No.	Description
79 002	2 m Arm, flexible exhaust arm
79 003	3 m Arm, flexible exhaust arm
79 004	4 m Arm, flexible exhaust arm
79 502	2 m Arm, rigid metal tube arm
79 503	3 m Arm, rigid metal tube arm
79 504	4 m Arm, rigid metal tube arm

