

## Exhaust Arm Upright -Suspended

### Applications

- » For existing devices
- » Non-stop operation
- » On work tables
- » On extraction devices
- » Welding fumes, gases, vapours, light dusts

### Benefits

- » Fast operation due to particularly flexible adjustment
- » 40% less adjustment of the exhaust arm needed due to exhaust hood design
- » User-friendly due to particularly smooth movement of the hood with one hand
- » Arm keeps position due to self-supporting design

### Properties

- » Polyester fabric hose, PVC coated with welded steel wire spiral
- » 360 degrees rotating exhaust hood with damper
- » Exhaust arms up to 4 m

### Scope of supply

- » Exhaust arm with hood
- » Swivel joint

- » 360° rotatable exhaust hood
- » Free moving operation



### Order Data

Art. No.	Description	Diameter	Exhaust arm type	Weight
<b>79 052</b>	2 m Arm, suspended installation	150 mm	flexible exhaust arm	17 kg
<b>79 053</b>	3 m Arm, suspended installation	150 mm	flexible exhaust arm	21 kg
<b>79 054</b>	4 m Arm, suspended installation	150 mm	flexible exhaust arm	24 kg
<b>79 102</b>	2 m Arm, upright installation	150 mm	flexible exhaust arm	17 kg
<b>79 103</b>	3 m Arm, upright installation	150 mm	flexible exhaust arm	21 kg
<b>79 104</b>	4 m Arm, upright installation	150 mm	flexible exhaust arm	24 kg

also available in rigid metal tube arm version

