

SmartMaster

- » Basic unit
- » Sporadic use



Applications

- » Also suitable for high-alloy steel
- » Low amounts of smoke/dust
- » Occasional use

Properties

- » W3/IFA certified
- » Handle with cable holder
- » Rotating exhaust hood

Benefits

- » Exhaust arm requires less adjustment due to exhaust hood design
- » Increased safety due to filter monitoring
- » Flexible use due to hose connection

Accessories

- » Suction hose with extraction nozzle

Technical Data

Filter	
Filter stages	3
Filter method	Disposable filter
Filter surface	ca. 13 m ²
Type of filter	Filter cassette
Filter material	Non-woven fibre
Filter efficiency	> 99.5 %
Filterclass	E12
Additional filters	Two pre-filters
Basic data	
Extraction capacity	950 m ³ /h
Dimensions (w x d x h)	705 x 655 x 900 mm
Weight	71 kg
Motor power	1.1 kW
Power supply	1 x 230 V / 50 Hz
Rated current	6.7 A
Noise level	72 dB(A)
Additional information	
IFA-Certification	W3-Approved
Fan type	Radial fan

Order Data

Art. No.	Description
64 300	2 m Arm, flexible exhaust arm
64 330	3 m Arm, flexible exhaust arm
64 310	3 m suction hose and nozzle
109 0452	Pre-filter mats (10 per set)
109 0454	Main filter 13 m ²
109 0453	Pre-filter cassette

