



TruTool TKA 500

Technical data

TruTool TKA 500 without tool

TruTool TKA 500 45° tool

MAXIMUM CHAMFER LENGTHS

MAXIMUM CHAMFER LENGTH, STEEL 400 N/MM ²	7 mm	7 mm
MAXIMUM CHAMFER LENGTH, STEEL 600 N/MM ²	3.7 mm	3.7 mm
MAXIMUM CHAMFER LENGTH, STEEL 800 N/MM ²	2.3 mm	2.3 mm
MAXIMUM CHAMFER LENGTH, ALUMINUM 250 N/MM ²	10 mm	10 mm

MAXIMUM CHAMFER HEIGHTS

MAXIMUM CHAMFER HEIGHT, STEEL 400 N/MM ²	4.9 mm	4.9 mm
MAXIMUM CHAMFER HEIGHT, STEEL 600 N/MM ²	2.5 mm	2.5 mm
MAXIMUM CHAMFER HEIGHT, STEEL 800 N/MM ²	1.6 mm	1.6 mm
MAXIMUM CHAMFER HEIGHT, ALUMINUM 250 N/MM ²	6.4 mm	6.4 mm

RADII

SMALLEST INNER RADIUS	18 mm	18 mm
-----------------------	-------	-------

GENERAL

MINIMUM SHEET THICKNESS	0.7 mm	0.7 mm
WORKING SPEED	3 m/min - 4 m/min	3 m/min - 4 m/min
NOMINAL INPUT POWER	1400 W	1400 W
REVOLUTION SPEED DURING IDLE RUN	8390 1/min	8390 1/min

WEIGHT

WEIGHT WITHOUT CABLE	3.5 kg	3.5 kg
----------------------	--------	--------

Subject to changes. The information in our offer and our order confirmation is definitive.