



# TruTool C 250 with chip clipper, Li-ion rechargeable battery 18 V

Technical data



## TruTool C 250 with chip clipper, Li-ion rechargeable battery 18 V

### MAXIMUM SHEET THICKNESSES

MAXIMUM SHEET THICKNESS, STEEL 400 N/MM <sup>2</sup>	2.5 mm
MAXIMUM SHEET THICKNESS, STEEL 600 N/MM <sup>2</sup>	1.5 mm
MAXIMUM SHEET THICKNESS, ALUMINUM UP TO 250 N/MM <sup>2</sup>	3 mm
SPIRAL DUCT, STEEL 400 N/MM <sup>2</sup>	4 x 0,9/ 6 x 0,6 mm
SPIRAL DUCT, STEEL 600 N/MM <sup>2</sup>	4 x 0.6 mm

### RADII

SMALLEST RADIUS	150 mm
-----------------	--------

### GENERAL

WORKING SPEED	3 m/min - 10 m/min
STROKE RATE DURING IDLE RUN	2400 1/min
STARTING HOLE DIAMETER	22 mm
VOLTAGE	18 V

### WEIGHT

WEIGHT (WITH 2 AH RECHARGEABLE BATTERY)	2.3 kg
WEIGHT (WITH 4 AH RECHARGEABLE BATTERY)	2.6 kg