

PS-15/ -30/ -50/ -75

Standard Valve Test Bench for Testing of Safety Valves and Shut-off / Control Valves



PS-15/-30/-50/-75 (with gantry)



PS-15/-30/-50/-75 (without gantry)

PS-15	PS-30	PS-50	PS-75
DN15 – DN250 (1/2" - 10")	DN25 – DN400 (500) (1" - 16"(20"))	DN25 – DN400 (500) (1" - 16"(20"))	DN25 – DN400 (500) (1" - 16"(20"))
For testing safety and shut-off valves and control valves			
For flanged, threaded and welded valves			
Clamping: stationary / vertical			
Test medium: air / nitrogen / water			
Hydraulic safety clamping system; prevents release of unit under test during pressurising			
Stainless steel water tank			
Test pressure generation via finely adjustable air-driven filling and high pressure pumps			
Long life as only high-quality components are used			
Clear and uncomplicated operation			
DN15 (1/2") max.200bar (2900psi)	DN25 (1") max.200bar (2900psi)	DN25 (1") max.200bar (2900psi)	DN25 (1") max.200bar (2900psi)
DN250 (10") max.25bar (362psi)	DN400 (16") max.16bar (232psi)	DN400 (16") max.25bar (362psi)	DN400 (16") max.45bar (653psi)
	DN500 (20") max.10bar (145psi)	DN500 (20") max.20bar (290psi)	DN500 (20") max.30bar (435psi)

Subject to technical change.

EFCO Maschinenbau GmbH – Valve repair and testing equipment

Otto-Brenner-Straße 5 – 7 • D - 52353 Düren • Phone: +49-(0)2421-989-0 • Fax: +49-(0)2421-86260

info@efco-dueren.de • sales@efco-dueren.de • www.efco-dueren.com

Agencies in many countries