

PS-SV15 / -30 / -50

Valve test bench for testing safety valves



PS-SV15	PS-SV30	PS-SV50
DN15 (1/2") – DN250 (10")	DN25 (1") – DN400 (16")	DN25 (1") – DN400 (16")
For testing safety valves		
For flanged and threaded valves		
Clamping: stationary / vertical		
Test medium: air / nitrogen		
Hydraulic safety clamping system; prevents release of unit under test during pressurising.		
Long life as only high-quality components are used.		
Clear and uncomplicated operation		
DN15 (1/2") max.200bar (2900psi)	DN15 (1/2") max.200bar (2900psi)	DN15 (1/2") max.200bar (2900psi)
DN250 (10") max.25bar (362psi)	DN250 (10") max.45bar (653psi)	DN250 (10") max.80bar (1160psi)
	DN400 (16") max.20bar (290psi)	DN400 (16") max.30bar (435psi)

Subject to technical change.

EFCO Maschinenbau GmbH – Valve repair and testing equipment

Otto-Brenner-Straße 5 – 7 • D - 52353 Düren • Phone: +49-(0)2421-989-0 • Fax: +49-(0)2421-86260

info@efco-dueren.de • sales@efco-dueren.de • www.efco-dueren.com

Agencies in many countries